


# BrixVision Content Extractor BV-2080V



Virtual video wall ideal for visual at-a-glance monitoring in the NOC, VOC, headend or via an ordinary browser

## KEY FEATURES

Thumbnail extraction of up to 100 concurrent services  
(300 channels per rackmount unit)

Both MPEG2 and MPEG4 decoding

Standard-definition and high-definition decoding

Freeze frame detection and alarming

Scrambling detection and alarming

Meta data extraction via XML over HTTP

The BV-2080V Content Extractor offers thumbnail and metadata extraction from up to 100 TV multicast streams concurrently via its Gigabit Ethernet interface (300 streams per rackmount unit). It is ideal for visual at-a-glance monitoring in the NOC, VOC, headend or via an ordinary browser remotely via any standard Web browser.

The BV-2080V is typically placed before scrambling insertion in the head-end, while the extracted metadata and decoded imagery is fed to the BrixVision live monitoring system. Disruption of descrambling services is one of the main causes for service production disruptions in the head-end and cost-effective monitoring of scrambling is now available.

The BV-2080V is equipped with Ethernet data input either as 10/100/1000T electrical or SFP-based optical and separate management is provided for data transfer. Its setup is similar to Brix video verifiers, via the built-in RS232 to USB converter.

Further applications are in middleware scenarios for generating channel mosaics or for extracting channel metadata such as picture resolution, video bandwidth or wide screen signaling information.

The BV-2080V Content Extractor card is specifically designed for the one-inch rackmount unit, which can house up to three Brix modules. This solution provides high-density decoding to thumbnails of up to 300 channels in a single unit.

## ADDITIONAL FEATURES

- › Thumbnail resolution: one-eighth size compared to original
- › Visual alarm icons inserted in thumbnails
- › Signal scrambled alarming
- › Freeze frame detection and alarming
- › Managed through BrixVision
- › Separate 10/100T management port
- › Electrical 10/100/1000T video port
- › Alternative SFP video port for optical connectivity
- › Protocol formats: nTS/UDP, nTS/RTP/UDP n=[1:7] (ETSI TS 102 034)

## SPECIFICATIONS

### Environment Specifications

- › Temperature
  - Operating: 0 °C to 50 °C (32 °F to 122 °F)
  - Storage: -20 °C to 70 °C (-4 °F to 158 °F)
- › Operating humidity: 5 % to 95 % non-condensing

### Connectors Specifications

- › 10/100/1000 Ethernet video: RJ-45
- › 10/100 Ethernet management: RJ-45
- › Optical input: SFP
- › USB port for initial setup (RS232 emulation)

### Power

- › Power dissipated by module: 12 W

### Network Specifications

- › 10/100/1000 BASE-T Ethernet (802.3u and 802.3ab)
- › SFP interface for optical networks
- › 10/100 BASE-TX Ethernet management (802.3u)

### Platform Specifications (platform sold separately)

- › Standard 19-inch rackmount unit
- › W x H x D: 483 mm x 43 mm x 400 mm
- › Weight: 4.2 kg fully populated
- › Power supply: 100-240 VAC (model BV-V-AC) or -48 VDC (model BV-V-DC)

### Control and Management

- › Basic setup/control through RS232 via USB
- › Remote access through HTTP or Telnet
- › Optional control via BrixVision Live Monitoring Software

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | [info@EXFO.com](mailto:info@EXFO.com)

Toll-free: +1 800 663-3936 (USA and Canada) | [www.EXFO.com](http://www.EXFO.com)

EXFO America	3701 Plano Parkway, Suite 160	Plano, TX 75075 USA	Tel.: +1 800 663-3936	Fax: +1 972 836-0164
EXFO Asia	151 Chin Swee Road, #03-29 Manhattan House	SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	36 North, 3 <sup>rd</sup> Ring Road East, Dongcheng District Room 1207, Tower C, Global Trade Center	Beijing 100013 P. R. CHINA	Tel.: +86 10 5825 7755	Fax: +86 10 5825 7722
EXFO Europe	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 2380 246810	Fax: +44 2380 246801
EXFO NetHawk	Elektroniikkatie 2	FI-90590 Oulu, FINLAND	Tel.: +358 (0)403 010 300	Fax: +358 (0)8 564 5203
EXFO Service Assurance	270 Billerica Road	Chelmsford, MA 01824 USA	Tel.: +1 978 367-5600	Fax: +1 978 367-5700

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit [www.EXFO.com/recycle](http://www.EXFO.com/recycle). Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at [www.EXFO.com/specs](http://www.EXFO.com/specs).

In case of discrepancy, the Web version takes precedence over any printed literature.